



FALL PROTECTION ANCHORAGE POINT



Reference	Diameter	Number of persons		Standard L ₁ (mm)	Torque (Nm)		S (mm)	A (mm)	B (mm)	C (mm)	D (mm)	Weight (kg)
		EN 795:2012	CEN/TS 16415:2013									
PE.SEB M 12	M 12 (x1,75)	1 pers.	2 pers.	21	15	35	6	30	34	60	57	0,24
PE.SEB M 16	M 16 (x2)	1 pers.	2 pers.	27	50	35	8	38	45	88	80	0,80
PE.SEB M 20	M 20 (x2,5)	1 pers.	2 pers.	30	100	35	8	38	45	88	80	0,80



Reference	Diameter	Number of persons		Standard L ₁ (mm)	Torque (Nm)		S (mm)	A (mm)	B (mm)	C (mm)	D (mm)	Weight (kg)
		EN 795:2012	CEN/TS 16415:2013									
SS.PE.SEB M 12	M 12 (x1,75)	1 pers.	2 pers.	21	15	35	8	38	45	90	80	0,80
SS.PE.SEB M 16	M 16 (x2)	1 pers.	2 pers.	27	50	35	8	38	45	90	80	0,82
SS.PE.SEB M 20	M 20 (x2,5)	1 pers.	2 pers.	30	100	35	8	38	45	90	80	0,84
SS.PE.SEB M 24	M 24 (x3)	1 pers.	2 pers.	36	150	50	8	38	45	90	80	0,90

