

# 115

## Pipe Laying Hook



- Carrying capacites up to 7,5 t
- Equipped with an automatic weight counterbalance
- For pipe lengths up to 3 m
- Equipped with a safety chain as standard

### Model RHK for pipe lengths up to 1 m



Order No.	Model	Carrying capacity	Throat width	Weight
		kg	mm	approx. kg
115 010 115 025	RHK 1/1 RHK 3/1	1000 3000	190 260	24 45

#### Model RHSV -

for pipe lengths up to 3 m, equipped with an automatic weight counterbalance and adjustable limit stop



Order	Model	Carrying	Throat	Min.	Weight
No.		capacity	width	Weight* approx.	annrov
	(7/	kg	mm	kg	approx. kg
115 210	RHSV 1/3	1000	300	350	180
115 325	RHSV 3/3	3000	460	1000	310
115 335	RHSV 7,5/3	7500	500	3000	732

\* For the functioning of the automatic system a minimum pipe weight for each RHSV pipe laying hook is necessary. Pipes with smaller weights cannot be handled with this equipment.

## 120

## Pipe Chain Sling With Hooks

The pipe chain sling with hooks is designed for easy and convenient loading and unloading of all types of pipes. It consists of two pipe hooks and a two-leg chain sling, whose lengths are designed to handle pipes up to 4 m.



All pipe chain slings with hooks are delivered with a 2-leg chain sling and a device for shortening and lengthening the chain sling for pipe lengths up to 4 m.

Order No.	Model for pipes of 4 m	Carrying capacity kg	Throat width approx. mm	Weight approx. kg
120 010	ROG 1/4	1000	200	31
120 020	ROG 2.5/4	2500	250	56
120 030	ROG 4/4	4000	320	101

For an additional charge rubber-lined throat width is available. In this way the throat width is reduced by 50 mm.

1.99 Subject to alteration.