

Montgomery Way Stratton Business Park Biggleswade Bedfordshire SG18 8QB

e-mail: sales@angliahandling.co.uk www.angliahandling.co.uk











## **U01-E**

Horizontal lifting of up to 75 kg with one suction pad.





## **U01-E**

lifting capacity / horizontal lifting



75 kg

suction pad layout



Ø 210 mm

load dimensions | material thickness (steel)



dead weight

5 kg

minimum load

5 kg

length x width x switching height

210 x 210 x 440 mm







The absolute classics among the VacuLifters - with a load capacity of up to 4,000 kg, completely based on the mechanical laws of physics: flexible and mobile, without any additional energy source.

The **U01-E** has a WLL of 75 kg. The minimum load dimension is  $210 \times 210$  mm. This Vaculifter is a light weight device with only 5 kg dead weight.

The energy-independent and mechanical systems for the horizontal transport of smooth and airtight materials are ready for immediate use. Whether indoors or outdoors, our self-suction vacuum lifters can be optimally tailored to your requirements.

They are primarily characterised by their ease of use. For example, the crane control or the automatic switching of the vacuum when putting on and taking off guarantee smooth transport. The sensitive surfaces are protected by the sealing ring made of high-quality rubber.

Equipped with an optical-acoustic warning unit, the self-sufficient VacuLifter® offer even greater safety in use.

Standards of all Green Line VacuLifter®

Energy-independent

- Standard and individual solutions
- 30 year guarantee on spare parts availability
- Made in Germany



www.vaculift.de