

Montgomery Way Stratton Business Park Biggleswade Bedfordshire SG18 8QB Tel: 01767-312125

e-mail: sales@angliahandling.co.uk www.angliahandling.co.uk











U125-8Q

Horizontal lifting of up to 1,200 kg with 8 suction pads.

Versatile. For a wide range of load dimensions. No need to compromise.





U125-8Q

lifting capacity / horizontal lifting



1,200 kg

suction pad layout



load dimensions | material thickness (steel)



dead weight

306 kg

minimum load weight

25 kg

length x width x switching height

3.200 x 1.400 x 1.300 mm









The absolute classics among the VacuLifters - with a load capacity of up to 4,000 kg, completely based on the mechanical laws of physics: flexible and mobile, without any additional energy source.

As the size of the loads can vary during operation, the U125-8Q is equipped with infinitely adjustable and lockable cross beams and suction pads. For even more variability in use, the outer suction pad pairs can be switched off manually via an easy-to-operate manual valve.

The **U125-8Q** is one of the most popular VacuLifter[®] and can be used for small to super formats from a thickness of 1 mm (reference: steel sheet).

They are primarily characterised by their ease of use. For example, the crane control or the automatic switching of the vacuum when putting on and taking off guarantee smooth transport. The sensitive surfaces are protected by the suction pads and sealing rings made of high-quality rubber.

Equipped with an optical-acoustic warning unit, the self-suction VacuLifter® offer even greater safety in use.

Standards of all Green Line VacuLifter®

Energy-independent

- Standard and individual solutions
- 30 year guarantee on spare parts availability
- Made in Germany

The VacuLifter® U125-8Q is available with a wide range of optional extensions such as an interchangeable set, a transport trolley, water separator, Ergo-Flex handle, a forklift traverse or with foldable parking supports available.