









U250-2

Horizontal lifting of up to 2,100 kg with 2 suction pads.



PERFORMANCE. NOTHING ELSE.



U250-2

lifting capacity / horizontal lifting




2,100 kg

suction pad layout



load dimensions | material thickness (steel)



dead weight

432 kg

minimum load weight

70 kg

length x width x switching height









The absolute classics among the VacuLifters - with a load capacity of up to 4,000 kg, completely based on the mechanical laws of physics: flexible and mobile, without any additional energy source.

Small traverse - large format. With the U250-2 comes the small beam for lifting large steel formats from 2 mm thick.

The energy-independent and mechanical systems for the horizontal transport of smooth and airtight materials are ready for immediate use. Whether indoors or outdoors, our self-suction vacuum lifters can be optimally tailored to your requirements.

They are primarily characterised by their ease of use. For example, the crane control or the automatic switching of the vacuum when putting on and taking off guarantee smooth transport. The sensitive surfaces are protected by the suction pads and sealing rings made of high-quality rubber.

Equipped with an optical-acoustic warning unit, the self-suction VacuLifter® offer even greater safety in use.

Standards of all Green Line VacuLifter®

Energy-independent

- Standard and individual solutions
- 30 year guarantee on spare parts availability
- Made in Germany

The VacuLifter® U250-2 is available with a wide range of optional extensions such as an interchangeable set, a transport trolley, water separator, a forklift traverse or with foldable parking supports available.



www.vaculift.de