








Safe Working Loads

				 0 - 90°		 0 - 90°		 0 - 90°	
Core	IWRC	Fibre Core		IWRC	Fibre Core		IWRC	Fibre Core	
Wire Rope Diameter	Single part with ferrule secured or spliced eyes	Single part with ferrule secured or spliced eyes	Double part endless or grommet	2 leg single part	2 leg single part	2 leg double part	3 or 4 leg single part	3 or 4 leg single part	3 or 4 leg double part
mm	tonnes	tonnes	tonnes	tonnes		tonnes		tonnes	
8 mm	0.82	0.76	1.1	1.1	1	1.5	1.7	1.6	2.3
9 mm	1	0.96	1.4	1.4	1.3	1.9	2.1	2	2.9
10 mm	1.3	1.2	1.8	1.8	1.7	2.5	2.7	2.5	3.8
11 mm	1.5	1.4	2.1	2.1	1.9	2.9	3.1	2.9	4.4
12 mm	1.8	1.7	2.5	2.5	2.4	3.5	3.8	3.5	5.2
13 mm	2.1	2	3	2.9	2.8	4.2	4.4	4.2	6.3
14 mm	2.5	2.3	3.5	3.5	3.2	4.9	5.2	4.8	7.3
16 mm	3.3	3	4.5	4.6	4.2	6.3	6.9	6.3	9.4
18 mm	4.1	3.8	5.7	5.7	5.3	8	8.6	8	11.9
19 mm	4.6	4.3	6.4	6.4	6	8.9	9.6	9	13.4
20 mm	5.1	4.7	7.1	7.1	6.6	9.9	10.7	9.8	14.9
22 mm	6.2	5.7	8.6	8.7	8	12	13	11.9	18
24 mm	7.4	6.8	10.2	10.3	9.5	14.3	15.5	14.3	21.4
26 mm	8.6	8	12	12	11	16.8	18	16.8	25.2
28 mm	10	9.3	14	14	13	19.6	21	19.5	29.4
32 mm	13.1	12.1	18.2	18.3	16.9	25.5	27.5	25.4	38.2
35 mm	15.7	14.5	21.8	22	20.3	30.5	33	30.4	45.8
36 mm	16.6	15.4	23.1	23.2	21.5	32.3	34.8	32.3	48.5
38 mm	18.5	17.1	25.7	25.9	23.9	36	38.8	35.9	53.9
40 mm	20.6	19	28.5	28.8	26.6	39.9	43.2	39.9	59.8