

## Flat Webbing Slings

Polyester webbing slings have many advantages over conventional chain or steel wire rope slings, particularly where the item to be lifted is in danger of being marked or damaged in the lifting process. The synthetic sling then comes into its own. The slings flexibility and ease of handling are appreciated by those involved in the lifting process and the wide load bearing surface aids safer lifting. Our slings are made from high strength polyester yarn incorporating good shock absorption properties with a high strength to weight ratio. Wear sleeves are available as an optional extra.


Polyester slings are suitable for use in a temperature range from - 40° C to + 100° C and are resistant to moderate strength acids. Do not use in alkali conditions. Seek our advice if exposure to chemicals is likely.

All our slings comply with BSEN 1492 part 1, are colour coded for increased safety with a Safety Factor of 7 : 1.

### Sling Types:


1. **Soft Reinforced Eyes Each End**
2. **Metal Eyes Each End**

### Simplex



Colour	Width mm	Straight x 1	Choked x 0.8	Basket x 2	45° Basket x 1.8	90° Basket x 1.4
		WLL kgs	WLL kgs	WLL kgs	WLL kgs	WLL kgs
Violet	30	500	400	1000	900	700
Violet	60	1000	800	2000	1800	1400
White	90	1500	1200	3000	2700	2100
Green	120	2000	1600	4000	3600	2800
Yellow	180	3000	2400	6000	5400	4200
Grey	240	4000	3200	8000	7200	5600
Red	300	5000	4000	10000	9000	7000

### Duplex



Colour	Width mm	Straight x 1	Choked x 0.8	Basket x 2	45° Basket x 1.8	90° Basket x 1.4
		WLL kgs	WLL kgs	WLL kgs	WLL kgs	WLL kgs
Violet	30 & 50	1000	800	2000	1800	1400
Green	60	2000	1600	4000	3600	2800
Yellow	90	3000	2400	6000	5400	4200
Grey	120	4000	3200	8000	7200	5600
Red	150	5000	4000	10000	9000	7000
Brown	180	6000	4800	12000	10800	8400
Blue	240	8000	6400	16000	14400	11200
Orange	300	10000	8000	20000	18000	14000

Other sizes available on request.