

Starpoint Eyebolts and Eyenuts



Metric Coarse Thread

Thread Size (mm)	Capacity 1 leg at 0° (tonnes)	Capacity 1 leg at 90° (tonnes)	Capacity 2 leg at 0° (tonnes)	Capacity 2 leg at 90° (tonnes)	Capacity 2 leg at 0-45° (tonnes)	Capacity 2 leg 45-60° (tonnes)	Capacity 3 + 4 leg 0-45° (tonnes)	Capacity 3 + 4 leg 45-60° (tonnes)
Method Of Lift								
M6	0.5	0.1	1	0.2	0.14	0.1	0.21	0.15
M8	1	0.3	2	0.6	0.42	0.3	0.63	0.45
M10	1	0.4	2	0.8	0.56	0.4	0.8	0.6
M12	2	0.7	4	1.5	1	0.7	1.5	1.1
M16	4	1.5	8	3	2.1	1.5	3.1	2.2
M20	6	2.3	12	4.6	3.2	2.3	4.8	3.4
M24	8	3.2	16	6.4	4.5	3.2	6.7	4.8
M30	12	4.5	24	9	6.3	4.5	9.4	6.7
M36	16	7	32	14	9.8	7	14.7	10.5
M42	24	9	48	18	12.6	9	18.9	13.5
M48	32	12	64	24	16.8	12	25	18

Imperial Thread

Thread Size (inches)	Capacity 1 leg at 0° (tonnes)	Capacity 1 leg at 90° (tonnes)	Capacity 2 leg at 0° (tonnes)	Capacity 2 leg at 90° (tonnes)	Capacity 2 leg at 0-45° (tonnes)	Capacity 2 leg 45-60° (tonnes)	Capacity 3 + 4 leg 0-45° (tonnes)	Capacity 3 + 4 leg 45-60° (tonnes)
Method Of Lift								
1/4	0.5	0.1	1	0.2	0.14	0.1	0.21	0.15
3/8	1	0.4	2	0.8	0.56	0.4	0.84	0.6
1/2	2	0.75	4	1.5	1.05	0.75	1.575	1.125
5/8	4	1.5	8	3	2.1	1.5	3.15	2.25
3/4	6	2.3	12	4.6	3.22	2.3	4.83	3.45
7/8	6	2.3	12	4.6	3.22	2.3	4.83	3.45
1	8	3.2	16	6.4	4.48	3.2	6.72	4.8
1. 1/4	12	4.5	24	9	6.3	4.5	9.45	6.75
1. 1/2	16	7	32	14	9.8	7	14.7	10.5
1. 3/4	24	9	48	18	12.6	9	18.9	13.5
2	32	12	64	24	16.8	12	25.2	18