



Hand Chain Blocks

Standard Hand Chain Block

	Capacity (kgs)	Closed Headroom (hook to hook)	Falls Of Chain	Mass (3 metre lift) (kg)
	250	230 mm	1	4
	500	305 mm	1	10.8
	1000	340 mm	1	12
	1500	385 mm	1	16.3
	2000	397 mm	1	16.7
	3000	465 mm	2	25
	5000	575 mm	3	39
	10000	735 mm	3	69.2
	20000	1000 mm	3	157.4


New Hand Chain Block (hand chain wheel rotates 360°)

	Capacity (kgs)	Closed Headroom (hook to hook)	Falls Of Chain	Mass (kgs) (3 metre lift)
	500	300 mm	1	9
	1000	335 mm	1	13
	2000	395 mm	1	20
	3000	520 mm	1	29
	5000	640 mm	2	38

A new innovative design with a 360 degree rotating hand chain guide that allows operation of the hoist from any position, even in extremely confined areas. This means greater options of working positions for the operator allowing the hoist to be operated from the side or even above the load. The hoist can also be used for horizontal pulling.

'Close Headroom' Combined Hand Chain Block & Trolleys

Available with a hand pushed or a hand geared trolley.

	Capacity (kgs)	Closed Headroom (under beam to hook)	Falls Of Chain	Beam Width (mm)		Mass (kgs) (3 metre lift)
				A	B	
	500	255 mm	1	50 - 180	180 - 300	18.8 / 20.8
	1000	290 mm	1	58 - 180	180 - 300	24.8 / 30.5
	2000	375 mm	2	58 - 180	180 - 300	37.5 / 41.7
	3000	465 mm	2	74 - 180	180 - 300	68 / 71
	5000	560 mm	2	98 - 180	180 - 300	103 / 109.2
	10000	760 mm	4	-	125 - 310	- / 175

Standard Trolleys

Push Travel	Capacity (kgs)	Beam Width (mm)	Geared Travel	Capacity (kgs)	Beam Width (mm)
	500	75 - 200		500	75 - 200
	1000	75 - 200		1000	75 - 200
	2000	75 - 250		2000	75 - 250
	3000	100 - 300		3000	100 - 300
	5000	100 - 300		5000	100 - 300
				10000	100 - 300
		20000	100 - 300		