



Manual and Powered Winches


Automatic Braked Winches

	Model	Max. Line Pull 1 st Layer (kg)	Max. Line Pull Full Drum (kg)	Rope Diameter (mm)	Rope Capacity (m)	Gear Ratio
	K650	270	90	3.2	26	1:1
	K1051	454	272	5.5	18	4.1:1
	KX1051	454	272	5.5	18	4.1:1
	K1550	682	320	6	27	5.1:1
	KX1550	682	320	6	27	5.1:1
	K2550	1136	680	8	23	15.8:1

Worm Gear Winches

	Capacity (kg)	Speed	Rope Diameter (mm)	Rope Capacity (m)	Weight (kg)
	250	1	5	20	9.5
	500	1	6.8	25	15
	1000	1	9	35	38
	1500	2	11.5	20	41.5
	2000	2	13	30	70
	3000	2	15	40	150


Spur Gear Winches

	Capacity (kg)	Speed	Rope Diameter (mm)	Rope Capacity (m)	Weight (kg)
	150	1	4	22	8
	300	1	5	40	16
	500	1	6.8	20	16
	1000	1	9	35	38
	2000	1	13	30	70

Powered Winches

A compact, general purpose 12-volt winch suitable for ATV's, trailers and lighter duty applications.

- 1135 kg rated line pull
- 3 stage planetary gearing
- Freespool clutch lever
- Permanent magnet motor
- Reliable and easy to use
- Strong automatic full load holding brake
- 14 m galvanised wire rope with hook
- 12 months warranty

	Max. Rated Line Pull	kgf	Cable Drum Capacity	m
	Layer 1	1135	Layer 1	2.1
	Layer 2	947	Layer 2	4.6
	Layer 3	815	Layer 3	7.6
	Layer 4	716	Layer 4	11.3