

Electric Chain Hoists



- Mains contactor as standard, for increased safety
- Thermal overload protection
- Duty cycle 50% ED for single speed
- 2 year warranty (excluding wear parts)
- Low voltage contactor control
- Insulated pendant control to IP65
- Hook path to suit your application
- Larger chain collectors available
- Upper and lower limit switches
- 3 phase and single phase supply

- Optional condition monitor
- Larger capacities available

The CPM electric chain hoists are available with capacities ranging from 125 to 2000 kg, CPE with capacities from 1600 to 10000 kg. Both types can be supplied with an eye suspension, hand pushed, hand geared or a power travel trolley.

Model	Capacity (kg)	Chain Falls	Hoist Headroom hook suspension (mm)	Hoisting Speed (m/min)	Power Travel Speeds single / dual (m/min)
CPM 1-8	125	1	317	8	14 / 14 & 3.5
CPM/F 1-8	125	1	317	8 & 2	14 / 14 & 3.5
CPM 2-8	250	1	317	8	14 / 14 & 3.5
CPM/F 2-8	250	1	317	8 & 2	14 / 14 & 3.5
CPM 5-4	500	2	397	4	14 / 14 & 3.5
CPM/F 5-4	500	2	397	4 & 1	14 / 14 & 3.5
CPM 5-8	500	1	365	8	14 / 14 & 3.5
CPM/F 5-8	500	1	365	8 & 2	14 / 14 & 3.5
CPM 10-4	1000	2	480	4	14 / 14 & 3.5
CPM/F 10-4	1000	2	480	4 & 1	14 / 14 & 3.5
CPM 10-8	1000	1	455	8	17 / 17 & 4.3
CPM/F 10-8	1000	1	455	8 & 2	17 / 17 & 4.3
CPM 20-4	2000	2	565	4	17 / 17 & 4.3
CPM/F 20-4	2000	2	565	4 & 1	17 / 17 & 4.3

CPE 16-8	1600	1	516	8	11 / 11 & 2.8
CPE/F 16-8	1600	1	516	8 & 2	11 / 11 & 2.8
CPE 20-8	2000	1	516	8	11 / 11 & 2.8
CPE/F 20-8	2000	1	516	8 & 2	11 / 11 & 2.8
CPE 25-5	2500	1	516	5	11 / 11 & 2.8
CPE/F 25-5	2500	1	516	5 & 1.25	11 / 11 & 2.8
CPE 30-5	3000	1	516	5	11 / 11 & 2.8
CPE/F 30-5	3000	1	516	5 & 1.25	11 / 11 & 2.8
CPE 32-4	3200	2	681	4	11 / 11 & 2.8
CPE/F 32-4	3200	2	681	4 & 1	11 / 11 & 2.8
CPE 40-4	4000	2	681	4	11 / 11 & 2.8
CPE/F 40-4	4000	2	681	4 & 1	11 / 11 & 2.8