

Demag Manulift Chain Hoist

Available in capacities of 125, 250 and 500 kg.

The Demag Manulift electric chain hoist incorporates the Up and Down pendant control buttons into the load hook to offer one handed operation, leaving the other hand free to guide the load.

The load hook is connected to the control block by a 'quick-release' bayonet coupling, so it can easily be removed and replaced by another standard attachment.

Standard attachments are shown below as well as a separate bayonet coupling that can be incorporated into a bespoke attachment and a load hook adaptor so the bayonet coupling system can be used on the hook of a standard hoist.



Model Options (Eye Suspension):

Capacity	Lifting Speeds	Hook Path *	Falls of Chain	Headroom *
125 kg	8 and 2 m/min	2800 / 4300 mm	1	694 / 764 mm
125 kg - variable	0.15 – 30 m/min	2800 / 4300 mm	1	694 / 764 mm
250 kg	8 and 2 m/min	2800 / 4300 mm	1	694 / 764 mm
250 kg - variable	0.15 – 16 m/min	2800 / 4300 mm	1	694 / 764 mm
500 kg	8 and 2 m/min	2800 / 4300 mm	1	746 / 816 mm
500 kg - variable	0.08 – 8 m/min	2800 / 4300 mm	1	746 / 816 mm