



Hydraulic Jacks


JH Hydraulic Bottle Jacks

	Model	Capacity (kgs)	Closed Height (mm)	Stroke (mm)	Screw Ext. (mm)	Weight (kgs)
	JH-2	2000	181	115	50	2.7
	JH-4	4000	205	126	60	3.7
	JH-6	6000	219	130	75	4.7
	JH-8	8000	225	152	70	5.7
	JH-12	12000	240	153	80	8.0
	JH-20	20000	240	153	80	11.0
	JH-30	30000	280	180	-	22.0
	JH-50/2	50000	305	178	-	53.0

YAM Hydraulic Claw Jacks

	Model	Claw Capacity (kgs)	Head Capacity (kgs)	Stroke (mm)	Weight (kgs)
	YAM-2	2000	2000	120	8
	YAM-5	5000	5000	120	19
	YAM-10	10000	10000	145	38
	YAM-15	15000	15000	120	41

AJH/S Aluminium Hydraulic Jacks

	<p>Aluminium jacks combine light weight with a high lifting capacity. The use of high tensile aluminium alloys allows lifting capacities of up to 100 tonnes resulting in a very favourable 1.8 tonnes lifting capacity per 1 kg weight ratio.</p>
	<p>AJH jacks are also available with a lifting claw - details and dimensions are available on request.</p>

Model	Capacity (tonnes)	Stroke (mm)	Closed Height (mm)	Base Plate Size (mm)	Weight (kgs)
AJS-653	6.5	75	131	159 x 76	3.6
AJS-104	10	115	182	171 x 76	6.3
AJH-620	20	152	265	180 x 120	10.9
AJH-1220	20	305	440	250 x 120	16.7
AJH-630	30	152	265	200 x 140	15.4
AJH-1230	30	305	452	275 x 140	23.4
AJH-660	60	152	293	250 x 190	17.4
AJH-1260	60	305	500	340 x 190	43.7
AJH-6100	100	152	315	305 x 250	49.0