

Duff-Norton Ratchet Jacks



5 to 20 Ton models

- Exclusive, patented, spring mechanism in one self-contained unit – can be adjusted, repaired or replaced without dismantling the jack.
- Load is moved one notch at a time – downstroke for raising, upstroke for lowering.
- Cannot be tripped under load.
- Rack bars can be hand-pulled to meet the load.
- Covers recessed in housing to protect the lifting mechanism.
- Fulcrum centres located for maximum speed and lifting ease.
- Curved tops standard on all units.
- Manufactured in compliance with ANSI B30.1.
- Each jack is operated under the rated capacity at the factory.
- 5 tonne available new, the remainder are available reconditioned with a full 12 month warranty.

Capacity (ton)	Height (inches)	Head Lift (inches)	Base (inches)	Head (inches)	Toe Lift	Rack Size (inches)	Weight (lbs)	Model Number
5	14	7½	5¼ x 7¾	2½ x 2¾	1½	1¼ x 1½	36	514-MT
5	16	9½	5¼ x 7¾	2½ x 2¾	1½	1¼ x 1½	41	515-MT
5	21	14½	5¼ x 7¾	2½ x 2¾	1½	1¼ x 1½	47	521-MT
10	22	12½	7 x 10¼	3 x 3	2	1½ x 1½	68	1022
15 / 7½	22	11½	8 x 11	3 x 3½	2½	1¾ x 2¼	100	1522
15 / 7½	28	17½	8 x 11	3 x 3½	2½	1¾ x 2¼	117	1528
20 / 10	28	18	8 x 11	3 x 3½	2½	1¾ x 2¼	126	2028

Roller Crow Bars

Available with steel or nylon rollers. Ideal for lifting, shifting and positioning of awkward loads.

Type	Steel Rollers	Nylon Rollers
	Capacity	5 tonnes
Length	1524 mm	1524 mm
Width	165 mm	165 mm
Wheel Diameter	76 mm	76 mm
Weight	15 kg	13 kg