

Anglia Handling Services Ltd.

Montgomery Way
Stratton Business Park
Biggleswade
Bedfordshire
SG18 8QB

Tel: +44 (0) 1767 312125
Fax: +44 (0) 1767 601375

sales@angliahandling.co.uk
www.angliahandling.co.uk

Biggleswade

SCAFFOLD HOISTS

HE 150 Veloce



Specifications:

| | |
|----------------------------|--------------------|
| Motor type: | Single phase |
| Voltage: | 110 v or 220 v |
| Frequency: | 50 Hz |
| Max. lifting capacity: | 150 kg |
| Engine power: | 1000 w |
| Lifting speed: | 33 m/min |
| Cable length: | 40 m |
| Steel cable diameter: | 4 mm |
| Cable breaking under load: | 11.28 kN |
| Hoist weight: | 40 kg |
| Dimensions: | 830 x 270 x 520 mm |
| Extended reach A frame: | 745 to 1120 mm |

HE 200



Specifications:

| | |
|----------------------------|--------------------|
| Motor type: | Single phase |
| Voltage: | 110 v or 220 v |
| Frequency: | 50 Hz |
| Max. lifting capacity: | 200 kg |
| Engine power: | 750 w |
| Lifting speed: | 23 m/min |
| Cable length: | 25 m |
| Steel cable diameter: | 5 mm |
| Cable breaking under load: | 23.26 kN |
| Hoist weight: | 37 kg |
| Dimensions: | 690 x 210 x 350 mm |

Continued...

Directors: A.Jefferies
K.J.Logue
D.Elleman



Registered in England No. 1545263
Vat Registration: 335 2809 59

Scaffold Hoists/

HE 200 RC



Specifications:

| | |
|----------------------------|--------------------|
| Motor type: | Single phase |
| Voltage: | 220 v |
| Frequency: | 50 Hz |
| Max. lifting capacity: | 200 kg |
| Engine power: | 750 w |
| Lifting speed: | 23 m/min |
| Cable length: | 25 m |
| Steel cable diameter: | 5 mm |
| Cable breaking under load: | 23.26 kN |
| Hoist weight: | 37 kg |
| Dimensions: | 690 x 210 x 350 mm |

HE 235



Specifications:

| | |
|-------------------------|--------------------|
| Motor type: | Single phase |
| Voltage: | 110 or 220 v |
| Frequency: | 50 Hz |
| Max. lifting capacity: | 200 kg |
| Engine power: | 750 w |
| Lifting speed: | 23 m/min |
| Cable length: | 35 m |
| Steel cable diameter: | 5 mm |
| Hoist weight: | 40 kg |
| Dimensions: | 830 x 270 x 520 mm |
| Extended reach A frame: | 745 to 1120 mm |

HE 200 Veloce



Specifications:

| | |
|------------------------|--------------------|
| Motor type: | Single phase |
| Voltage: | 110 or 220 v |
| Frequency: | 50 Hz |
| Max. lifting capacity: | 200 kg |
| Engine power: | 1350 w |
| Lifting speed: | 39 m/min |
| Cable length: | 40 m |
| Steel cable diameter: | 5 mm |
| Hoist weight: | 39 kg |
| Dimensions: | 690 x 210 x 350 mm |

Continued...

Directors: A.Jefferies
K.J.Logue
D.Elleman



Registered in England No. 1545263
Vat Registration: 335 2809 59

Scaffold Hoists/

HG 200 Inverter



Specifications:

| | |
|------------------------|---------------------|
| Motor type: | Single phase |
| Voltage: | 220 v |
| Frequency: | 50 Hz |
| Max. lifting capacity: | 200 kg |
| Engine power: | 2000 w |
| Lifting speed: | 7-13-20-33-45 m/min |
| Cable length: | 50 - 100 m |
| Steel cable diameter: | 5 mm |
| Hoist weight: | 58 kg |
| Dimensions: | 830 x 270 x 520 mm |

HG 200



Specifications:

| | |
|------------------------|--------------------|
| Motor type: | Single phase |
| Voltage: | 110 or 220 v |
| Frequency: | 50 Hz |
| Max. lifting capacity: | 200 kg |
| Engine power: | 900 w |
| Lifting speed: | 23 m/min |
| Cable length: | 50 - 100 m |
| Steel cable diameter: | 5 mm |
| Hoist weight: | 53 kg |
| Dimensions: | 800 x 300 x 435 mm |