

# Trolley clamp CTP

## Trolley clamp model CTP

Capacities 1.000 - 3.000 kg

The easy installation to any beam makes the CTP suitable for affixing and moving hoists, pulleys and loads. It can be adjusted quickly to the beam width by turning the main spindle.

Safety is ensured by the special locking lever.

The spindle and snap-pin stops are galvanized to protect against corrosion.



Model	Capacity kg	Flange width b mm	Min. curve radius m	Weight kg
CTP 1 - A	1000	60 - 150	0,6	2,5
CTP 2 - A	2000	75 - 200	0,9	9,9
CTP 2 - B	2000	200 - 300	0,9	10,3
CTP 3 - A	3000	75 - 200	1,15	17,5
CTP 3 - B	3000	200 - 320	1,15	19,5

Capacity kg	Size	A mm	D mm	E mm	H <sub>1</sub> mm	I mm	L mm	L <sub>1</sub> mm	M mm	O mm	P mm	T mm	t max. mm
1000	A	82 - 109	26	22	20	53	160	75	M12	46	153	105	15
2000	A	106 - 155	42	20	30,0	71,5	260	130	M18	60	205	139	25
2000	B	136 - 191	42	20	30,0	71,5	260	130	M18	60	255	189	25
3000	A	128 - 171	50	22	30,5	95,5	310	150	M24	80	220	155	25
3000	B	150 - 212	50	22	30,5	95,5	310	150	M24	80	280	215	25

