




Manhole Lifting Devices

Manhole Clamp – type SZ

Ideal for the transport and laying of manholes. Clamp adjusts automatically to wall thickness.

	Capacity (kg)	Clamps	Jaw Surface	Clamping Range (mm)	Manhole I/D (mm)	Web Length (mm)	Weight (kg)
	1000	2	Steel	40 - 120	800 - 2000	1450	16
	2000	2	Steel	60 - 180	800 - 2000	1450	28

	Capacity (kg)	Clamps	Jaw Surface	Clamping Range (mm)	Manhole I/D (mm)	Web Length (mm)	Weight (kg)
	1500	3	Steel	40 - 120	800 - 2000	1450	28
	1500	3	Steel	40 - 120	800 - 2800	2050	27
	3000	3	Steel	60 - 180	800 - 2000	1450	40
	3000	3	Steel	60 - 180	800 - 2800	2050	41
4000	4	Steel	60 - 180	800 - 2500	1450	55	

	Capacity (kg)	Clamps	Jaw Surface	Clamping Range (mm)	Manhole I/D (mm)	Chain Length (mm)	Weight (kg)
	1500	3	Steel	40 - 120	800 - 2000	1450	33
	3000	3	Steel	60 - 180	800 - 2000	1450	45
3000	3	Steel	60 - 180	800 - 3000	2200	47	




Manhole Grabs – type RSV

A rubber coated jaws are needed for smooth, painted or coated manholes.

	Capacity (kg)	Clamps	Jaw Surface	Clamping Range (mm)	Manhole I/D (mm)	Chain Length (mm)	Weight (kg)
	1500	3	Steel	40 - 120	400 - 2000	1500	31
	1500	3	Steel	40 - 120	400 - 3000	2000	33
	1500	3	Rubber Coat	0 - 70	400 - 2000	1500	34
	3000	3	Steel	50 - 180	400 - 2000	1600	53
	3000	3	Steel	50 - 180	400 - 3000	2200	57
	3000	3	Rubber Coat	0 - 130	400 - 2000	1600	55
	3000	3	Steel	90 - 230	400 - 2000	1600	54
	3000	3	Steel	90 - 230	400 - 3000	2200	58
	3000	3	Rubber Coat	50 - 180	400 - 2000	1600	56
	1000	2	Steel	40 - 120	-	800	10
	2000	2	Steel	50 - 180	-	800	17
	4000	4	Steel	50 - 180	1000 - 2500	1600	82

Manhole Cover Lifter – type KH

Designed to lift manhole covers using a hydraulic cylinder. Easy to dismantle and transport in a car boot.

			Capacity (kg)	Lifting Height (mm)	Hook Distance	Total Width (mm)	Weight (kg)
			1000	250	260 - 980	1200	30

Complete with a set of hooks type A and B