









## Specialist Lifting Eye Range

| Type             | Swivel Key Eye Point  |   | Swivel Hoist Ring Type 231  |   | Lifting Point  |   | Swivel Hoist Ring Type 203  |   |
|------------------|---|---|---|---|--|---|---|---|
|                  |  |   |  |   |  |   |  |   |
| Thread Size (mm) | Capacity 1 leg at 90° (tonnes)  | Capacity 1 leg at 0° (tonnes)   | Capacity 1 leg at 90° (tonnes)  | Capacity 1 leg at 0° (tonnes)   | Capacity 1 leg at 90° (tonnes)   | Capacity 1 leg at 0° (tonnes)   | Capacity 1 leg at 90° (tonnes)  | Capacity 1 leg at 0° (tonnes)   |
| Method Of Lift   |  |  |  |  |  |  |  |  |
| M8               | -   | -   | 0.50  | 0.50  | 0.3  | 0.3   | 0.50  | 0.50  |
| M10              | 0.40  | 1.00  | 0.70  | 0.70  | 0.63   | 0.63  | 0.55  | 0.55  |
| M12              | 0.75  | 2.00  | 1.00  | 1.00  | 1.00   | 1.00  | 1.30  | 1.30  |
| M14              | -   | -   | 1.50  | 1.50  | 1.20   | 1.20  | -   | -   |
| M16              | 1.50  | 4.00  | 2.00  | 2.00  | 1.50   | 1.50  | 2.40  | 2.40  |
| M18              | -   | -   | 2.50  | 2.50  | 2.00   | 2.00  | -   | -   |
| M20              | 2.30  | 6.00  | 3.00  | 3.00  | 2.50   | 2.50  | 2.70  | 2.70  |
| M24              | 3.20  | 8.00  | 5.00  | 5.00  | 4.00   | 4.00  | 5.25  | 5.25  |
| M27              | -   | -   | 5.60  | 5.60  | 4.00   | 4.00  | -   | -   |
| M30              | 4.50  | 12.00   | 7.80  | 7.80  | 5.00   | 5.00  | 8.75  | 8.75  |
| M36              | 7.00  | 16.00   | 12.50   | 12.50   | 7.00   | 7.00  | 13.75   | 13.75   |
| M42              | 9.00  | 24.00   | 15.60   | 15.60   | 10.00  | 10.00   | 15.60   | 15.60   |
| M48              | 12.00   | 32.00   | 20.00   | 20.00   | 20.00  | 20.00   | 16.90   | 16.90   |
| M56              | -   | -   | 22.00   | 22.00   | -  | -   | -   | -   |
| M64              | -   | -   | 22.50   | 22.50   | -  | -   | -   | -   |

| (UNC)   | (lbs) | (lbs) | (lbs) | (lbs) | (lbs) | (lbs) | (lbs) | (lbs) |
|---------|-------|-------|-------|-------|-------|-------|-------|-------|
| 5/16"   | -     | -     | -     | -     | -     | -     | 800   | 800   |
| 3/8"    | -     | -     | -     | -     | -     | -     | 1000  | 1000  |
| 1/2"    | -     | -     | -     | -     | 2200  | 2200  | 2500  | 2500  |
| 5/8"    | -     | -     | -     | -     | 3300  | 3300  | 4000  | 4000  |
| 3/4"    | -     | -     | -     | -     | 5500  | 5500  | 5000  | 5000  |
| 7/8"    | -     | -     | -     | -     | 5500  | 5500  | 8000  | 8000  |
| 1"      | -     | -     | -     | -     | 8800  | 8800  | 10000 | 10000 |
| 1. 1/4" | -     | -     | -     | -     | 11000 | 11000 | 15000 | 15000 |
| 1. 1/2" | -     | -     | -     | -     | 17000 | 17000 | 24000 | 24000 |
| 1. 3/4" | -     | -     | -     | -     | 33000 | 33000 | -     | -     |
| 2"      | -     | -     | -     | -     | 44000 | 44000 | 30000 | 30000 |

□ Please contact us for capacities on different slinging methods.