


Electric Chain Hoists *(capacities from 125 – 6,300 kg)*



- ✓ Mains contactor as standard, for increased safety
 - ✓ Low voltage 48v contactor control
 - ✓ Insulated pendant control to IP65
 - ✓ Hook path to suit your application
 - ✓ Larger chain collectors available
 - ✓ 3 phase and single phase supply
 - ✓ Slower 10 m/min travel speed also available
- Optional upper and lower limit switches
 - Optional radio remote control
 - Optional stainless steel load chain
 - Optional special paint for hostile environments
- Spark Resistant  also available

Our standard range of electric chain hoists are available with capacities ranging from 125 to 6300 kg, which can be **supplied with a hook suspension, hand pushed, hand geared or a power travel trolley.**

Model	Capacity (kg)	Chain Falls	FEM	Headroom (mm)	Hoisting Speed (m/min)	Power Travel Speeds single / dual (m/min)	
ST 0501-8/2 1/1	125	1	3m (M6)	367	8 & 2	20	20 & 5
ST 0501-16/4 1/1	125	1	2m (M5)	367	16 & 4	20	20 & 5
ST 0502-8 1/1	250	1	1Am (M4)	367	8	20	20 & 5
ST 0502-8/2 1/1	250	1	1Am (M4)	367	8 & 2	20	20 & 5
ST 0502-8 2/1	500	2	1Am (M4)	428	4	20	20 & 5
ST 0502-8/2 2/1	500	2	1Am (M4)	428	4 & 1	20	20 & 5
ST 1005-8 1/1	500	1	1Am (M4)	372	8	20	20 & 5
ST 1005-8/2 1/1	500	1	1Am (M4)	372	8 & 2	20	20 & 5
ST 1005-8 2/1	1000	2	1Am (M4)	432	4	20	20 & 5
ST 1005-8/2 2/1	1000	2	1Am (M4)	432	4 & 1	20	20 & 5
ST 2010-8 1/1	1000	1	2m (M5)	467	8	20	20 & 5
ST 2010-8/2 1/1	1000	1	2m (M5)	467	8 & 2	20	20 & 5
ST 3016-8 1/1	1600	1	1Bm (M3)	509	8	20	20 & 5
ST 3016-8/2 1/1	1600	1	1Bm (M3)	509	8 & 2	20	20 & 5
ST 3216-8/2 1/1	1600	1	1Bm (M3)	557	8 & 2	20	20 & 5
ST 2010-8 2/1	2000	2	2m (M5)	547	4	20	20 & 5
ST 2010-8/2 2/1	2000	2	2m (M5)	547	4 & 1	20	20 & 5
ST 5025-6/1 1/1	2500	1	1Am (M4)	586	6.3 & 1.5	20	20 & 5
ST 5025-8/2 1/1	2500	1	1Am (M4)	586	8 & 2	20	20 & 5
ST 3016-8 2/1	3200	2	1Bm (M3)	575	4	20	20 & 5
ST 3016-8/2 2/1	3200	2	1Bm (M3)	575	4 & 1	20	20 & 5
ST 3216-8/2 2/1	3200	2	2m (M5)	657	4 & 1	20	20 & 5
ST 5025-6/1 2/1	5000	2	1Am (M4)	697	3.2 & 0.75	20	20 & 5
ST 5025-8/2 2/1	5000	2	1Am (M4)	697	4 & 1	20	20 & 5
ST 6032-6/1.5 2/1	6300	2	1Bm (M3)	697	3.2 & 0.75	20	20 & 5

Please note that the 'Headroom' dimension is for a hoist with hook suspension.