


Aluminium Gantries and Tripods


Ideal for site changes. The gantry is easily erected by one person due to link between beam and supports.

Fold out the four supports, secure with bolts and adjust to the height required. Supplied with an erection aid.


Fixed Adjustable Height Aluminium Gantry - type 530

	Safe Working Load:	750 or 1500 kg
	Overall Height:	1870 - 3080 mm
	Overall Width:	4115 mm
	Trolley Suspension Height:	1510 - 2720 mm
	Weight:	85 kg
Supplied with a top running hand pushed trolley.		

Mobile Adjustable Height Aluminium Gantry - type 535

	Safe Working Load:	1000 kg
	Overall Height:	2400 - 3200 mm
	Overall Width:	4000 mm
	Trolley Suspension Height:	2000 - 2800 mm
	Weight:	130 kg
Supplied with a top running hand pushed trolley.		

Fixed Adjustable Height Aluminium Tripod

	<ul style="list-style-type: none"> ✓ Light Aluminium construction ✓ Telescopic legs for compact transportation ✓ Spiked feet as standard ✓ Swivel suspension eye
	<ul style="list-style-type: none"> ▪ Optional rubber feet for solid ground ▪ Optional safety chain for smooth ground

Model	Capacity (kg)	Length of Support L Min/Max. (mm)	Clearance Height H Min/Max. (mm)	Spreading Angle B Min/Max. (mm)	Weight (kg)
D-250	250	1180 / 1880	940 / 1580	950 / 1500	10
D-500	500	1500 / 2500	1150 / 2050	1200 / 1950	17
D-500/En795	500	1500 / 2500	1150 / 2050	1200 / 1950	17
D-503	500	1760 / 3000	1450 / 2630	1430 / 2390	20
D-1000	1000	1780 / 3000	1380 / 2540	1650 / 2350	27
D-1004	1000	2250 / 4000	1860 / 3440	1790 / 3070	36

- i) Maximum spreading angle (25°).
- ii) Permitted for man riding applications up to 150 kg according to EN 795. Equipped with rubber plates and safety chain.