



Pipe Hooks and Safety Hook


Pipe Laying Hooks

	Capacity (kg)	Pipe Length (mm)	Throat Width (mm)	Weight (kg)
	1000	up to 1000 mm	190	24
	3000	up to 1000 mm	260	45


Pipe Laying Hooks – Automatic Counterbalance

	Capacity (kg)	Pipe Length (mm)	Throat Width (mm)	Weight (kg)
	350 - 1000	up to 3000 mm	300	180
	1000 - 3000	up to 3000 mm	460	310

Pipe Laying Hooks - Chain Sling Suspension

	Capacity (kg)	Pipe Length (mm)	Throat Width (mm)	Weight (kg)
	2500	up to 4000	250	56
	4000	up to 4000	320	101

Pipe Laying Hooks - Chain Sling Suspension

	Capacity (kg)	Leg Angle (mm)	Wall Thickness (mm)	Weight (kg)
	2000	60 - 90	0 - 40	2.4
	4000	60 - 90	0 - 50	5.6
	6000	60 - 90	0 - 60	8.3
	8000	60 - 90	0 - 70	13.5
	10000	60 - 90	0 - 80	17.8

	Capacity (kg)	Leg Angle (mm)	Wall Thickness (mm)	Weight (kg)
	2000	90 - 120	0 - 30	2.4
	4000	90 - 120	0 - 40	5.6
	6000	90 - 120	20 - 50	8.3
	8000	90 - 120	35 - 65	13.5
	10000	90 - 120	30 - 75	17.8

Automatic Safety Hook – available in 2, 5, 10, 15 and 20 tonne

Automatically hooks up, safety locks and releases so the risk of injury is dramatically reduced.

