



Hydraulic Jacks

JH Hydraulic Bottle Jacks


	Model	Capacity (kgs)	Closed Height (mm)	Stroke (mm)	Screw Ext. (mm)	Weight (kgs)
	JH-2	2000	181	115	50	2.7
	JH-4	4000	205	126	60	3.7
	JH-6	6000	219	130	75	4.7
	JH-8	8000	225	152	70	5.7
	JH-12	12000	240	153	80	8.0
	JH-20	20000	240	153	80	11.0
	JH-30	30000	280	180	-	22.0
	JH-50/2	50000	305	178	-	53.0

Hydraulic Claw Jacks

	Model	Claw Capacity (kgs)	Head Capacity (kgs)	Closed Height (mm)	Stroke (mm)	Weight (kgs)
	BVA-3	3000	3000	16 / 230	130	17.8
	BVA-6	6000	6000	22 / 267	130	27.2
	BVA-10	10000	10000	28 / 280	130	39.5
	BVA-15	15000	15000	28 / 332	130	54.3

Features include a low toe height and a large base area.

AJH/S Aluminium Hydraulic Jacks

	Aluminium jacks combine light weight with a high lifting capacity. The use of high tensile aluminium alloys allows lifting capacities of up to 100 tonnes resulting in a very favourable 1.8 tonnes lifting capacity per 1 kg weight ratio.					
	Capacity: 6.5 to 100 tonne without toe					
	Capacity: 20 to 60 tonne with toe					

Model	Capacity Head (tonnes)	Capacity Toe (tonnes)	Stroke (mm)	Closed Height (mm)	Base Plate Size (mm)	Weight (kgs)
AJS-653	6.5	-	75	131	159 x 76	3.6
AJS-104	10	-	115	182	171 x 76	6.3
AJH-620-toe	20	8	152	280	250 x 120	67
AJH-1220-toe	20	8	305	452	250 x 120	67
AJH-630-toe	30	12	152	284	275 x 140	72
AJH-1230-toe	30	12	305	472	275 x 140	72
AJH-660-toe	60	24	152	327	340 x 190	72
AJH-1260-toe	60	24	305	533	340 x 190	72